



2746e

Thermal, On-demand Metal Bar Code Printer

Durable Metal Value

The new-generation 2746e represents an affordable, basic bar code print solution for light-industrial companies new to bar coding that will benefit from a sturdy, steel-enclosed, on-demand printer. Revamped electronics and improved ribbon spindle design significantly improve the 2746e's overall reliability and quality.

Enhanced Connectivity, More Capabilities

The 2746e offers internal or external Ethernet, plus serial, parallel, and USB interfaces for easy system integration. Dual processors deliver fast throughput for greater productivity, while increased memory handles more complex labels and allows easy firmware upgrades. Easy-to-use design includes standard rewind and peel, as well as new maintenance and media tracking features for ensured reliable performance, such as printhead life odometer, printhead reminder control, and clear media window. Add up all these high-quality capabilities, and you've got one exceptional value!

The metal 2746e is ideal for a range of applications in warehousing and distribution, air freight, manufacturing, and general office environments. Able to print individual labels or full-roll batches, it handily meets the printing needs of small to medium-size businesses, such as:

- Shipping/Receiving
- Inventory control
- Asset tracking
- Bulk mailing



Connect with it. Count on it.™

2746e



Specifications at a Glance*

STANDARD FEATURES

Print methods: Direct thermal and thermal transfer
Construction: Steel enclosure
1 MB Flash; 512 KB SRAM memory
Dual processors
Rewind and peel
Label present sensor for peel mode
Selectable print speeds: 3"/76 mm, 4"/102 mm, 5"/127 mm, or 6"/152 mm per second
Media sensor for black marks, see through, die-cut labels and label out
Rear feed slot for fanfold or oversized roll label-stock
Auto-calibration/color-coded cues
Diagnostics and configuration print-out and ASCII dump
Windows® drivers (95, 3.xx, NT v.3.51, NT v.4.0)
Windows printer utilities

Programming

Communicates in printable ASCII characters
Compatible with mainframe, mini and PC hosts
Four position field rotation (0°, 90°, 180°, 270°)
Variable field support (00 to 99)
Counter support (up to 10)
Variable field addition and subtraction
Status reporting
Form storage
Metered print odometer

OPERATING CHARACTERISTICS

Environment

Operating Temp. 32° F/0° C to 105° F/40° C
Storage/Transport Environ. -40° F/-40° C to 140° F/60° C
Operating Humidity 10-90% non-condensing
Ventilation Free air

Electrical

Input: 120 VAC; 60 Hz or 240 VAC; 50 Hz

Communication Interface Capabilities

USB Version 1.1
Serial RS232 (DB9)
4.8-57.6K bits/second
Flow control: Xon/Xoff or DTR/DSR, hardware selectable
Parallel (Centronics)
LAN/Ethernet (requires optional ZebraNet® PrintServer II)

Agency Approvals

FCC, UL, CE, VCCI, CB, C-Tic, EN55022, CISPR22B, EN50082-1, EN60950, IEC 950

MEDIA CHARACTERISTICS

Labels

Max. Roll Size: 8"/203 mm O.D. on a 3"/76 mm I.D. core
Thickness (label & liner): .003"/.08 mm to .010" (0.25 mm)
Media Types: Roll-feed, die-cut, continuous, fanfold; tags; tickets
For optimum print quality and print engine performance, use Genuine Zebra supplies.

Ribbons

Max. Roll Size: 3.3"/84 mm O.D. on a 1"/25.4 mm I.D. core
Standard Ribbon Length: 14,200" (360 m)
Ribbon Set-up: Ribbon wound ink side out
Ribbon is recommended to be at least as wide as media.

Fonts/GRAPHICS/SYMBOLOLOGIES

Fonts and Character Sets

5 alphanumeric fonts—expandable vertically and horizontally
Fonts can be printed in 4 directions: 0°, 90°, 180° and 270° degrees
IBM Code Page 850 International Characters
Asian language support (optional)
Soft font storage in Flash memory

Graphic Features

Line and box drawing
PCX graphic storage

Bar Code Symbolologies

Linear bar codes: Code 39, Extended Code 39, Code 93, Code 128 with subsets B and C
UCC/EAN-128, UPC Container code, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Postnet, German Postal Code, Standard 2 of 5, Interleaved 2 of 5, Codabar
2-dimensional bar codes: PDF417, Maxi Code, QR Code (Asian Only)

OPTIONS AND ACCESSORIES

ZebraNet PrintServer II (for Ethernet connectivity)—available in internal or external variety
Keyboard display unit (KDU)
Asian language support
Real-time clock
Windows label design software

The 2746e's durable metal frame and ease of use make it the perfect starter printer.

MAXIMUM PRINT AREA

Width: 4.09"/104 mm
Length: 22"/558 mm

RESOLUTION

203 dpi/8 dots per mm

MAXIMUM PRINT SPEED

6"/152 mm per second

MEMORY

Standard 1 MB Flash; 512 KB SRAM

PHYSICAL CHARACTERISTICS

Width: 9.5"/241 mm
Depth: 16.75"/425 mm
Height: 12.38"/314 mm
Weight: 28.6 lbs (13 kg)

MEDIA SPECIFICATIONS

Label and liner thickness: 0.003"/.0762 mm to 0.010" (0.25 mm)
Ribbon Width: 1.3"/34 mm to 4.3"/110 mm

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.

HEADQUARTERS

Zebra Technologies International, LLC **PHONE:** +1 847.634.6700 or +1 800.423.0442 **FAX:** +1 847.913.8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin **EUROPE:** Denmark, France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea **LATIN AMERICA:** Argentina, Brazil
MIDDLE EAST: United Arab Emirates



An ISO 9001 registered company
©2002 ZIH Corp.
Printed in U.S.A.
#11164L Rev. 4 (12/02) 5M